



Clamps & Hose Products

General Purpose				Lined Clamps				Constant Torque			
P/N	Min. Dia.	Max. Dia.		P/N	Min. Dia.	Max. Dia.		P/N	Min. Dia.	Max. Dia.	
62040 51	7/32"	5/8"		5736 051	1-13/16	2-3/4		6506E-51	9/16"	13/16"	
62060 51	1/4	25/32		5740 051	2-1/16	3		6508E-51	11/16	15/16	
5706 051	7/16	25/32		5744 051	2-5/16	3-1/4		6510E-51	13/16	1-1/16	
5708 051	1/2	29/32		5748 051	2-9/16	3-1/2		6512E-51	15/16	1-1/4	
5710 051	9/16	1-1/16		5752 051	2-13/16	3-3/4		6516E-51	13/16	1-1/2	
5712 051	11/16	1-1/4		5756 051	3-1/16	4		6520E-51	13/16	1-3/4	
5716 051	13/16	1-1/2		5764 051	3-9/16	4-1/2		6524E-51	1-1/16	2	
5720 051	13/16	1-3/4		5772 051	1-7/8	5		6528E-51	1-5/16	2-1/4	
5724 051	1-1/16	2		5782 051	3-1/8	6		6532E-51	1-9/16	2-1/2	
5728 051	1-5/16	2-1/4		5796 051	3-5/8	6-1/2		6536E-51	1-13/16	2-3/4	
5732 051	1-9/16	2-1/2						6540E-51	2-1/16	3	

NEW

NEW



HOSE BARB FITTINGS



BELTS



GOODYEAR
ENGINEERED PRODUCTS

Need Release® Extended Service Coolant Filter

- Eliminates over-inhibited cooling systems
- Reduces cost
- Minimizes waste



Universal 3-Way Test Strips

The first & only test strip designed for all heavy-duty coolant types. A quick & effective way to test your cooling system in both conventional & extended life coolant.

25 test strips/bottle

TS200



Antifreeze with SCA Pencoool



- Prestone**
2087-40 Fuschia, 1 Gallon Antifreeze
2087-15 Fuschia, 55 Gallon Antifreeze
- Shamrock**
2087M-40 Fuchsia, 1 Gallon Pre-Mixed 50/50
2087M-15 Fuchsia, 55 Gallon Pre-Mixed 50/50



Premium Hy-T Black - 50 Ft. Rolls

Hy-T black heater hose meets SAE J20R3 specifications.

- GY65000 1/2"
- GY65004 5/8"
- GY65009 3/4"
- GY65012 1"

Premium Hy-T Red

Hy-T heater hose is made with a tough Versigard rubber cover & tube to resist heat, ozone, & anti-freeze solutions. Built to withstand the pressure of today's automobiles' trucks, & busses. Minimum burst pressure of 140 PSI. Expands easily over heater connections, resists tearing & splitting. Available in red cover-up through 3/4" I.D. Premium Hy-T Red heater hose meets SAE J20R3 specifications.

- GY65020 1/2"
- GY65023 5/8"
- GY65026 3/4"



Hi-Miler 50 Ft. Rolls




Hi-Miler is outstanding for strength & heat resistance. Made with high temperature Versigard synthetic rubber. Reinforced with heat-resistant Flesten cored that is pound for pound, stronger than steel. Built to outlast standard heater hose without the cost of more expensive silicone hose. Readily recognizable blue cover. Meets SAE J20R3 specifications.

- GY65028 3/8"
- GY65029 1/2"
- GY65031 5/8"
- GY65033 3/4"
- GY65035 1"
- GY65037 1-1/4"


Hump Hose

For Air Inlet Systems



P/N	I.D.	Length
34-35	3.5"	5.25"
34-4	4	5.25"
34-5	5"	6"
34-6	6"	7"

Rubber Reducers




35-54
5" ID1 x 4" ID2 x 5.5" L

35-554
5.5" ID1 x 4" ID2 x 6" L

35-655
6" ID1 x 5.5" ID2 x 6" L

Rubber Reducing Elbow 90°

6" D-1 x 5.50" D-2



38-655

Air Inlet Clamps

Stainless Steel T-Bolt type allows flexible assembly of rubber elbows & aluminum tubing



P/N	Dia.
30011 0250 051	2.5"
30011 0300 051	3"
30011 0350 051	3.5"
30011 0400 051	4.0"
30011 0500 051	5.0"
30011 0550 051	5.5"
30011 0650 051	6"
30011 0700 051	7.0"



Spring Loaded T-Bolt Clamp

P/N	Dia.
30030 0356	3 9/16" - 3 7/8"
30030 0406	4 1/16" - 4 3/8"
30030 0456	4 9/16" - 4 7/8"

NEW


Rubber Elbows

For Air Inlet Systems



90°	45°
32-390 - 3" ID	33-345 - 3" ID
32-590 - 5" ID	33-445 - 4" ID
32-690 - 6" ID	33-545 - 5" ID
	33-645 - 6" ID

SILICONE CHARGE AIR COOLER HOSE (CAC)



- 6" Hot side CAC hose
- 4-Ply aramid reinforced with high strength restrictor rings
- For superior connection between engine mounted charge air systems components
- Ideal for handling slight misalignments & isolating vibration between hose ends

P/N	I.D.	O.D.
44-250	2.50	2.71
44-300	3.00	3.21
44-3035	3.00/3.50	3.21/3.71
44-350	3.50	3.71
44-3540	3.50/4.00	3.71/4.21
44-400	4.00	4.21

CLAMPS FOR SILICONE HOSE



Lined Hose Clamps

- Stainless Steel Band, Saddle, & Housing
- 5/16" Hex Screw
- Recommended application up to 40 lbs-in torque
- Seal silicone & other soft hoses without damage
- Inner Liner Extends under the perforations to protect the hose & prevents extrusions through the worm gear perforations



P/N	Min. to Max. Size (Inches)
5340 051	2-1/16 - 3
5344 051	2-5/16 - 3-1/4
5348 051	2-9/16 - 3-1/2
5352 051	2-13/16 - 3-3/4
5360 051	3-5/16 - 4-1/4

NEW

Clamps_Hose



HDA TRUCK PRIDE



MIDWESTWHEEL.COM

Iowa

DES MOINES
1436 E. Ovid Ave.
OFFICE 515.265.1491
FAX 515.265.4120
PARTS FAX 800.314.4329
PARTS 800.888.0248

CEDAR RAPIDS
200 50th Ave. S.W.
MAIN 319.365.4453
FAX 319.365.6327
PARTS FAX 877.706.6085
PARTS 800.332.5435

DAVENPORT
8502 Northwest Blvd.
MAIN 563.322.2671
FAX 563.322.5940
PARTS fax 800.553.1886

TRUCK PARTS SUPER STORE™

CLEAR LAKE
840 Hwy. 18 W.
MAIN 641.357.7101
FAX 641.357.8190
PARTS FAX 800.548.9674
PARTS 800.397.5630

SIoux CITY
1819 E. 4th St.
MAIN 712.252.7969
FAX 712.252.6149
PARTS FAX 800.943.3534

Missouri

KANSAS CITY
5801 E. Front St.
MAIN 816.471.1552
FAX 816.471.0813
PARTS 800.821.7402

GRANDVIEW
14817 So. 71 Hwy.
MAIN 816.318.9111
FAX 816.318.9114
PARTS 866.318.9111