



NEW LOWER PRICING!



Air Shield Diesel Exhaust Fluid



Air Shield™ DEF is a urea-based chemical reactant designed specifically for use in SCR systems to reduce NOx emissions.

729566
2.5 Gallon

749714
55 Gallon Drum

728802
330 Gallon Tote

DEF Pumping Systems

3/4" Automatic Shutoff Nozzle



906006-83
\$144.05

3/4" x 12' Hose w/NPT Fitting



150200-01
\$58.81

DEF Refractometer

Simple new kit verifies DEF concentration for proper SCR performance

Most heavy duty diesel engines made in 2010 utilize SCR technology to meet 2010 emission regulations. The SCR system uses DEF to function properly. Our new simple-to-use DEF Refractometer quickly verifies the correct ratio of 32.5% Urea/Water solution to ensure proper SCR operation. The last thing you need on the open road is a loss of power due to low DEF concentration.



OT 5025
\$69.99

DEF Hand Pumps



Hand Pump

Model LP50
Portable hand pump that can be used to easily help pump Urea or any other Diesel Exhaust Fluid

Designed to fit tanks or 55-gallon barrels with 2" NPT threads.

The LP-50 ensures a smooth and easy stroke eliminating side load or shaft binding.

129000-1
\$69.84

Polypropylene Rotary Barrel Pump




Model 8075

- High-density polypropylene with Ryton vanes
- Three-piece extension tube with filter and 2" bung adapter
- Use with water, water-based chemicals, 50/50 antifreeze mix, windshield washer solvents, alcohol, gasoline, diesel fuel, and DEF fluid!

8075
\$91.99

DEF Digital Meters



113255-24
\$178.71

Specifically designed with DEF, this nylon turbine meter is calibrated in gallons with NPT threads.

Inlet: 1 in.
Flow Range: 3 to 30 GPM
10 to 100 LPM

*All Needed Fittings Included



Most accurate and versatile agricultural chemical meter on the market. Factory calibrated for thin and medium to thick fluids, even

oils. Electronic Disc Meter in flow range 2 to 20 GPM (7 to 75 LPM) with LCD readout. Displays gallons.

Inlet: 1 in.
Flow Range: 2 to 20 GPM
7 to 75 LPM

120000-32
\$269.26

*All Needed Fittings Included

DEF Transfer Pumps

115 volt AC DEF Pump for chemical such as Urea. Flow range up to 12 GPM (45 LPM). Two inch tank connection. order hose and nozzle separately. Includes adjustable suction pipe.



118450-01
\$643.50

Inlet: 1 in.
Flow Rate: 3 to 30 GPM
10 to 100 LPM
Voltage & Type: 115 Volt AC Gear Pump

12 volt DC Plastic Gear Pump specifically designed for use with DEF. Includes suction pipe and 20 foot power cable

118450-02
\$480.56

Inlet: 1 in.
Flow Range: 3 to 30 GPM
10 to 100 LPM
Voltage & Type: 12 Volt DC Gear Pump



NOTE: When using pumps for a 330 gallon tote please use part #115527-2. This is a suction pipe extension that will reach the bottom of the tank.

September 2011 (PumpingSystems)



MIDWESTWHEEL.COM

Iowa

DES MOINES
1436 E. Ovid Ave.
OFFICE 515.265.1491
FAX 515.265.4120
PARTS FAX 800.314.4329
PARTS 800.888.0248

**TRUCK PARTS
SUPER STORE™**

CEDAR RAPIDS
200 50th Ave. S.W.
MAIN 319.365.4453
FAX 319.365.6327
PARTS FAX 877.706.6085
PARTS 800.332.5435

DAVENPORT
8502 Northwest Blvd.
MAIN 563.322.2671
FAX 563.322.5940
PARTS fax 800.553.1886

CLEAR LAKE
840 Hwy. 18 W.
MAIN 641.357.7101
FAX 641.357.8190
PARTS FAX 800.548.9674
PARTS 800.397.5630

SIOUX CITY
1819 E. 4th St.
MAIN 712.252.7969
FAX 712.252.6149
PARTS FAX 800.943.3534

Missouri

KANSAS CITY
5801 E. Front St.
MAIN 816.471.1552
FAX 816.471.0813
PARTS 800.821.7402

GRANDVIEW
14817 So. 71 Hwy.
MAIN 816.318.9111
FAX 816.318.9114
PARTS 866.318.9111